

PRODUCT DATASHEET

DST COMP 8 W/827 E27

OSRAM DULUXSTAR COMPACT | CFLi, stick shape, with screw base



TECHNICAL DATA

Electrical data

Rated wattage	8.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	39 W
Nominal wattage	8.00 W
Power factor λ	≥ 0.55
Nominal current	0.08 A
Operating frequency	50...60 Hz


Photometrical data

Nominal luminous flux	390 lm
Rated luminous flux	390 lm
Rated color temperature	2700 K
Light color	827
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	390 lm
Color rendering index Ra	≥ 80

Light technical data

Warm-up time (60 %)	< 40.00 s
Starting time	≤ 0.3 s

Dimensions & weight



Maximum diameter	41.0 mm
Overall length	114.0 mm
Product weight	53.00 g
Length	114.0 mm

Lifespan

Nominal lamp life time	6000 h
Rated lamp life time	6000 h
Number of switching cycles	10000

Additional product data

Base (standard designation)	E27
Mercury content	2.0 mg
Show WEEE picto	Yes

Capabilities

Dimmable	No
----------	----

Certificates & standards

Energy consumption	8 kWh/1000h
Energy efficiency class	A
Cleaning instruction in case of breakage	What to do if a lamp containing mercury breaks?

Country-specific categorizations

ILCOS	FBT-8/27/1B-220/240-E27
-------	-------------------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321112651	Folding carton box 1	43 mm x 43 mm x 120 mm	0.07 g	0.22 dm ³
4008321874849	Shipping carton box 20	226 mm x 189 mm x 136 mm	1490.00 g	5.81 dm ³
4052899263017	Folding carton box 1	44 mm x 44 mm x 117 mm	81.00 g	0.23 dm ³
4052899449411	Shipping carton box 10	226 mm x 95 mm x 136 mm	730.00 g	2.92 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.